

## Product variant: autoLock AV4D standard

Number of auxiliary locking points: 2

### Product details for multi-point locking system

- Solid steel hooks with claw action and 25 mm unbolting length, as well as sealing elements for dynamic contact pressure
- Smooth unlocking via offset opening of the locking elements – even with installation tolerances
- Solid hooks in fully locked position secured against being pushed back
- Motorised electric strike function can be retrofitted to the lock face plate using EAV4/EAV4+ motor housing
- With brass main deadbolt, matt chrome-plated mc/silver-coloured coating
- With zinc-steel latch, matt chrome-plated mc/silver-coloured coating
- Prepared for installation of all profile cylinders corresponding to DIN 18252 or DIN EN 1303 (corrosion class C) generally with cam position  $\pm 45^\circ$
- Lock housing closed on all sides, suitable for all common door plates/rosettes in accordance with DIN 18251, recommended for use of a handle set with fixed knob/pull/push handle (outside), handle (inside)
- Cam load-free in locked position for easier key insertion
- Optional for Swiss round cylinders (e.g. Kaba)
- **AV4D/Key operated:**  
Manual actuation of the main deadbolt via the profile cylinder with single-turn locking design (approx.  $1 \times 360^\circ$  key rotation) and simultaneous handle blocking for increased security (holiday lockout function)

### Certification and standardisation

- Security door lock according to DIN 18251- 3, class 4 (safety-relevant characteristics)
- VDS test, class B
- Hook in accordance with PAS 23/24
- Suitable for burglary-resistant doors according to DIN EN 1627-30 RC 2

### Product details for frame parts

- Standard individual keeps (or extension keep sets/keep rails) with integrated pressure adjustment
- Latch/bolt keep (or keep rails) with adjustable latch plate and central magnetic release
- Fail-safe device via frame-side magnetic trigger
- Daytime latch can be retrofitted as an option



**A** Multi point locking system | autoLock AV4D/Automatic | autoLock AV4D standard

**B** Keep rail | Keep rail standard | Hook

**B** Extension keep set | Extension keep rail standard | Hook

**C** Single keep | Main locking system keep | Latch-deadbolt

**D** Single keep | Auxiliary locking system keep | Hook